

RECEIVED
CENTRAL FAX CENTER

MAY 21 2007

Serial No. 10/616,067
Page 2 of 10

IN THE CLAIMS

1. (currently amended) An outer-loop power control device in which a reference signal-to-interference power ratio, which is the a basis of transmission power control by a communications environment, is variable, comprising:

a signal-to-interference power ratio measurement unit measuring a signal-to-interference power ratio of a receiving signal;

an error rate measurement unit measuring an error rate of receiving data;

a reference signal-to-interference power ratio modification unit setting an observation time period of an error rate/number of target observation blocks of an-the error rate, a unit increment of a reference signal-to-interference power ratio, a unit decrement of a-the reference signal-to-interference power ratio and a target signal error rate in such a way to satisfy a prescribed relation equation changing a unit change value of increment or decrement of the reference signal-to-interference power ratio according to the measured error rate and modifying the reference signal-to-interference power ratio, based on the measured error rate; and

a command generation unit generating a command for transmission power control by comparing the modified reference signal-to-interference power ratio with the measured interference power ratio.

2. (original) The outer-loop power control device according to claim 1, wherein if the target signal error rate, the observation time period, the unit increment, and the unit decrement are assumed to be BLER, T, Sinc, and Sdec, respectively, the relation equation can be expressed as follows.

$$\{1 - (1 - \text{BLER})^T\} \times \text{Sinc} = (1 - \text{BLER})^T \times \text{Sdec}$$

84216619_1

Serial No. 10/616,067

Page 3 of 10

3. (currently amended) The outer-loop power control device according to claim 1, wherein if a plurality of pieces of data are multiplexed in one physical frame and if ~~the a~~ number of multiplexed data, the target signal error rate of the data number, the observation time period, the unit increment, and the unit decrement are assumed to be i , $BLER_i$, T , $Sinc$, and $Sdec$, respectively, the relation equation can be expressed as follows.

$$[1 - \{ \prod_i (1 - BLER_i) \}^T] \times Sinc = \{ \prod_i (1 - BLER_i) \}^T \times Sdec$$

4. (original) The outer-loop power control device according to claim 1, wherein if a plurality of pieces of data are multiplexed in one physical frame, if each piece of multiplexed data has a different number of blocks per unit time period N_i , and if the number of multiplexed data, the target signal error rate of the data number, the observation time period, the unit increment, and the unit decrement are assumed to be i , $BLER_i$, T , $Sinc$, and $Sdec$, respectively, the relation equation can be expressed as follows.

$$[1 - \{ \prod_i (1 - BLER_i)^{N_i} \}^T] \times Sinc = \{ \prod_i (1 - BLER_i)^{N_i} \}^T \times Sdec$$

5. (currently amended) The outer-loop power control device according to claim 1, wherein if a plurality of pieces of data are multiplexed in one physical frame and if ~~the an~~ amount of multiplexed data, where the target signal error rate of ~~the a~~ data number, the observation time period, the unit increment corresponding to the data number, and the unit

84216619_1

Serial No. 10/616,067

Page 4 of 10

decrement corresponding to the data number are assumed to be i , $BLER_i$, T_i , $Sinc_i$, and $Sdec_i$,

respectively, the relation equation can be expressed as follows.

$$\{1 - (1 - BLER_i)^{T_i}\} \times Sinc_i = (1 - BLER_i)^{T_i} \times Sdec_i$$

6. (currently amended) The outer-loop power control device according to claim 1, wherein if a plurality of pieces of data are multiplexed in one physical frame, if each piece of multiplexed data has a different number of blocks per unit time period N_i , and if ~~the~~an amount of multiplexed data, where the target signal error rate of ~~the~~a data number, the observation time period, the unit increment corresponding to the data number, and the unit decrement corresponding to the data number are assumed to be i , $BLER_i$, T_i , $Sinc_i$, and $Sdec_i$, respectively, the relation equation can be expressed as follows.

$$\{1 - (1 - BLER_i)^{N_i \times T_i}\} \times Sinc_i = (1 - BLER_i)^{N_i \times T_i} \times Sdec_i$$

7. (original) The outer-loop power control device according to claim 1, wherein if data blocks are irregularly transmitted/received, if each observation time period has a different number of transmitted/received data blocks, and if the number of data blocks observed during the observation time period, the target signal error rate, the unit increment, and the unit decrement are assumed to be B , $BLER$, $Sinc$, and $Sdec$, respectively, the relation equation can be expressed as follows.

$$\{1 - (1 - BLER)^B\} \times Sinc = (1 - BLER)^B \times Sdec$$

8. (currently amended) The outer-loop power control device according to claim 1, wherein if data blocks are irregularly transmitted/received, if each observation time period has a

84216619_1

Serial No. 10/616,067

Page 5 of 10

different number of transmitted/received data blocks, and if ~~the~~an amount of multiplexed data, the target signal error rate of the a data number, the number of data blocks of the received data number, the unit increment and the unit decrement are assumed to be i , $BLER_i$, B_i , $Sinc$, and $Sdec$, respectively, the relation equation can be expressed as follows.

$$[1 - \prod_i (1 - BLER_i)^{B_i}] \times Sinc = \prod_i (1 - BLER_i)^{B_i} \times Sdec$$

9. (currently amended) The outer-loop power control device according to claim 1, wherein if a plurality of pieces of data are multiplexed in one physical frame, if data blocks are irregularly transmitted/received, if each observation time period has a different number of transmitted/received data blocks, and if ~~the~~an amount of multiplexed data, the target signal error rate of the a data number, the number of data blocks of the received data number, the unit increment corresponding to the data number and the unit decrement corresponding to the data number are assumed to be i , $BLER_i$, B_i , $Sinc_i$, and $Sdec_i$, respectively, the relation equation can be expressed as follows.

$$[1 - (1 - BLER_i)^{B_i}] \times Sinc_i = (1 - BLER_i)^{B_i} \times Sdec_i$$

10. (currently amended) The outer-loop power control device according to claim 1, wherein in an initial state of communications, ~~a~~the reference signal-to-interference power ratio can be modified by a larger unit amount than a unit modification amount of a reference signal-to-interference power ratio in a stable state before a prescribed number of times of data error are observed.

84216619_1

Serial No. 10/616,067

Page 6 of 10

11. (currently amended) The outer-loop power control device according to claim 1, wherein the observation time period of an error rate/number of target observation blocks of ~~an~~ the error rate, unit increment of a reference signal-to-interference power ratio and unit decrement of ~~a~~ the reference signal-to-interference power ratio that satisfy the relation equation are constituted into a table ~~excluding at most one item of the items~~ and using ~~a~~ the target signal error rate as a key, and the observation time period/number of target observation, unit increment and unit decrement can be obtained by referring to the table.

12. (currently amended) An outer-loop power control method in which a reference signal-to-interference power ratio, which is the basis of transmission power control by a communications environment, is variable, comprising:

measuring a signal-to-interference power ratio of a receiving signal;

measuring an error rate of receiving data;

setting an observation time period of an error rate/number of target observation blocks of ~~an~~ the error rate, a unit increment of a reference signal-to-interference power ratio, a unit decrement of ~~a~~ the reference signal-to-interference power ratio and a target signal error rate in such a way to satisfy a prescribed relation equation changing a unit change value of increment or decrement of the reference signal-to-interference power ratio according to the measured error rate and modifying the reference signal-to-interference power ratio, based on the measured error rate; and

generating a command for power transmission control by comparing the modified reference signal-to-interference power ratio with the measured interference power ratio.

84216619_1

Serial No. 10/616,067

Page 7 of 10

13. (original) An outer-loop power control device in which a reference signal-to-interference power ratio, which is the basis of transmission power control by a communications environment, is variable, comprising: a signal-to-interference power ratio measurement unit measuring a signal to interference power ratio of a receiving signal; a reference signal-to-interference power ratio modification unit varying the reference signal-to-interference power ratio based on measurement result of an error rate in a measurement time period of the error rate and changing the reference signal-to-interference power ratio to a large value without waiting for an end of the measurement time period when an error of a signal is detected in the measurement time period; and a command generation unit generating a command signal for transmission power control by comparing the modified reference signal-to-interference power ratio with the measured interference power ratio.

84216619_1